



# DIVER CONSOLIDATED INDUSTRIES

PROPRIETOR DIVER METAL PRODUCTS PTY. LTD

## Specifications of QuietSheet™ Diamond

<b>Appearance/ Description</b>	Single layer dimpled aluminium material, with adhesive butyl backing
<b>Temperature Range</b>	
<b>Minimum Continuous</b>	0°C
<b>Maximum Continuous</b>	200°C
<b>Melting Point</b>	255°C
<b>Thickness</b>	2.3mm Nominal
<b>Weight</b>	3.02 kg/m <sup>2</sup>
<b>Flexibility</b>	Great
<b>Flammability</b>	Flammable (Butyl)
<b>Ignition Temperature (flash point)</b>	>255°C
<b>RoHS</b>	Yes
<b>Halogen Free</b>	Yes
<b>Toxicity</b>	Slightly Toxic Butyl contains - Ethylene Glycol 1-5% - Quartz Silica 0.1-1%
<b>Binders</b>	No
<b>Acoustic Absorption Coefficients</b>	Not Available  Butyl is a vibration dampening material; sound absorption is not a direct by-product of its use.

This data sheet and contained specifications exists solely for the user to determine the suitability of this product for specific use. The contents contained are derived from DCI testing procedures and Diver Metal Products PTY. LTD. makes no warranties as to their accuracy or completeness. Diver Metal Products PTY. LTD. will not be liable for any consequential or other damages arising from use or miss-use of their products



**THERMAL & ACOUSTIC PRODUCTS DIVISION**  
MANUFACTURERS OF HEAT AND NOISE MANAGEMENT PRODUCTS,  
THERMAL AND ACOUSTICS SHIELDS  
45 TRAWALLA AVENUE, THOMASTOWN, VICTORIA 3074  
Nat Ph: (03) 9357 2511 Nat Fax: (03) 9359 2191  
Inter Ph: 61 3 9359 2191 Inter Fax: 61 3 9359 2191

